

DP-1332G-SH HD-TVI DVR



Features and Functions


- Connectable to TVI and analog cameras;
- Support DUNLOP protocol for connecting camera over coax;
- Connectable to network cameras;
- Simultaneous HDMI and VGA outputs at up to 1920×1080p resolution;
- New GUI and supports starting record with one key;
- Redundant recording, holiday recording schedule configuration;
- Instant playback for assigned camera during multi-channel live view mode;
- Support up to 24/32-ch synchronous playback; and reverse playback for multi-channel;
- Smart playback to go through less effective information;
- Manual video quality diagnostics;
- Support VCA alarm (line crossing detection and intrusion detection);
- Customization of tags, searching and playing back by tags;
- Locking and unlocking record files;
- Support HDD quota and group management; different capacity can be assigned to different cameras under quota mode;
- Provide 4 SATA interfaces and 1 eSATA interface for record and backup;
- 1 self-adaptive 10M/100M/1000M network interface;
- Support access by EZVIZ Cloud P2P;
- Support Hikvision DDNS (Dynamic Domain Name System);
- Network detection function.



Specifications

Model		DP-1332G-SH
Video/ Audio input	Video compression	H.264
	Analog and HD-TVI video input	32-ch BNC interface (1.0Vp-p, 75 Ω)
	Supported camera types	720p/25, 720p/30, 720p/50, 720p/60, 1080p/25, 1080p/30, CVBS
	IP video input	8-ch (up to 32-ch)
		Up to 2MP resolution
	Audio compression	G.711u
	Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)
Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)	
Video/ Audio output	HDMI / VGA output	1920 × 1080/60 Hz ,1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
	Encoding resolution	Main stream: 1080p (non-real-time)/720p/WD1/VGA/4CIF/CIF
		Sub-stream: WD1 (non-real-time)/4CIF (non-real-time)/CIF/QCIF/QVGA
	Frame rate	Main stream: 1/16 fps to Real time frame rate
		Sub-stream: 1/16 fps to Real time frame rate
	Video bitrate	32 Kbps to 6 Mbps
	Audio output	1-ch, RCA (Linear, 1KΩ)
	Audio bitrate	64 Kbps
	Dual-stream	Support
	Stream type	Video, Video & Audio
Synchronous playback	32-ch	
Playback resolution	1080p/720p/VGA/WD1/4CIF/CIF/QVGA/QCIF	
Network management	Remote connection	128
	Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Hard disk	Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface
	Capacity	Up to 6TB capacity for each disk
External interface	Network interface	1; 10M/100M/1000M self-adaptive Ethernet interface
	Serial interface	RS-232, RS-485, Keyboard
	USB port	3 × USB 2.0
	Alarm in / out	16/4
General	Power supply	100 to 240 VAC, 47 to 63 HZ
	Consumption (without hard disks)	≤ 65W
	Working temperature	-10°C to +55°C (14°F to 131°F)
	Working humidity	10% to 90%
	Chassis	19-inch rack-mounted 1.5U chassis
	Dimensions (W × D × H)	445 × 390 × 70 mm (17.5 × 15.3 × 2.7 inch)
Weight (without hard disks)	≤ 5 Kg (11.0lb)	

Physical Interfaces



Index	Description	Index	Description
1	VIDEO IN	9	RS-485 Serial Interface, Keyboard Interface, ALARM IN and ALARM OUT
2	AUDIO IN, RCA Connector	10	100 to 240 VAC Power Input
3	USB Port	11	Power Switch
4	HDMI Interface	12	GND
5	VGA Interface	13	LINE IN
6	VGA AUDIO OUT	14	eSATA Interface
7	LAN Network Interface	15	RS-232 Serial Port
8	VIDEO IN		