

DP-22CD4035F


3MP Smart IP Box Camera



Key features

- Up to 2048 x 1536 high resolution
- Full HD1080p video
- Smart Codec
- 3D DNR
- Triple streams
- On-board storage, up to 64GB
- Smart Focus: ABF(-A)
- Smart VQD
- Smart Facial Detection
- Smart Audio Detection
- Intrusion Detection
- Two way audio,built-in Mic
- Defog
- P-Iris optional(-P)

Dimensions



DP-22CD4035F	
Camera	
Image sensor	Progressive scan cmos
Min. Illumination	Color: 0.05 Lux @ (f1.2, Agc on) B/w: 0.005 Lux @ (f1.2, Agc on)
Shutter speed	1 S to 1/100,000 s
Slow shutter	Support
Lens mount	C/cs mount
Auto-iris	Ds drive (p iris: -p model)
Day & night	Ir cut filter with auto switch
Digital noise reduction	3D dnr
Wide dynamic range	Dwdr
Compression standard	
Video compression	H.264/ Mjpeg
H.264 Type	Baseline profile / main profile / high profile
Video bit rate	32 Kbps – 16 mbps
Audio compression	G.711/G.722.1/G.726/Mp2l2
Audio bit rate	64Kbps(g.711) / 16Kbps(g.722.1) / 16Kbps(g.726) / 32-128Kbps(mp2l2)
Image	
Max. Resolution	2048X1536
Main stream	50Hz: 50fps (2048 × 1536,1920 × 1080,1280 × 720) 60Hz: 48fps@ (2048 × 1536), 60fps (1920 × 1080,1280 × 720)
Third stream	Independent with main stream and sub stream, up to 50Hz: 25fps (2048 × 1536) 60Hz: 30fps (2048 × 1536)
Blc	Support
Hlc	Support
Defog	Support
Image setting	Rotate mode, saturation, brightness, contrast are adjustable by client software or web browser
Day/night switch	Auto/schedule/triggered by alarm in
Roi	Support
Picture overlay	128X128 24bit bmp format overlay, zone optional
Network	
Network storage	Nas (support nfs,smb/cifs)
Alarm trigger	Intrusion detection, defocus detection, motion detection, face detection, dynamic analysis, tampering alarm, network disconnect, ip address conflict, storage exception
Protocols	Top/ip,icmp,http,https,ftp,dhcp,dns,ddns,rtp,rtsp,rtpc, Pppoe,ntp,upnp.smtp.snmp.igmp,802.1X,qos.ipv6,bonjour
Security	User authentication, watermark, ip address filtering, anonymous access
Standard	Onvif, psia, cgi, isapi
Interface	
Audio input	1-Ch 3.5 Mm audio interface, mic in/line in. 1 Build-in microphone
Audio output	1-Ch 3.5 Mm audio interface
Communication interface	1 Rj45 10m/100m ethernet port, 1 rs-485 interface and 1 rs-232 interface
Alarm input	1
Alarm output	1
Video output	1Vp-p composite output (75 Ω/bnc)
On-board storage	Built-in micro sd/sdhc/sdxc slot, up to 64 gb
Reset button	Yes
Smart feature-set	
Behavior analysis	Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal
Line crossing detection	Cross a pre-defined virtual line
Intrusion detection	Enter and loiter in a pre-defined virtual region
Region entrance	Enter a pre-defined virtual region from the outside place
Region exiting	Exit from a pre-defined virtual region
Unattended baggage	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Object removal	Objects removed from the pre-defined region, such as the exhibits on display.
Exception detections	Scene change detection, sudden audio increase/decrease detection, audio loss detection, defocus detection
Recognition	Face detection recognition
Statistics	Object counting (entrance and exit object number is accounted and showed on screen in real time)
General	
Operating conditions	-30 °C – 60 °C (-22 °f – 140 °f) Humidity 95% or less (non-condensing)
Power supply	24 V ac ± 10%, 12 v dc ± 10%, poe (802.3Af)
Power consumption	Max. 6 W (max. 9W with ir cut filter on)
Dimensions	69.8×58×145 Mm (2.68" × 2.56" × 5.70")
Weight	830g (1.83 lbs)