

## DP-22D14WD



### Genel Özellikler

- 1.0 megapiksel (1280 x 720 @ 30 fps) çözünürlük
- ROI (region of interest) kodlama
- 100 dB WDR
- Progressive scan CMOS
- IR cut filtresi
- 3D DNR
- Dual stream ve mobil gözetleme için sub-stream desteği
- BLC ve elektronik shutter desteği
- Mini dizayn
- Heartbeat, mirror, watermark, etc
- İzinsiz giriş ve alan işgal tespiti
- VCA desteği

### Uygulama Alanları:

Bu ürün ATM gibi gözetlemenin gizlice yapılmasının gerekli olduğu yerlerde kullanılmaya uygundur.

### Özellikler:

Model	DP-22D14WD
Parametre	1.0 Megapiksel CMOS WDR Mini Network Kamera
Kamera	
Resim Sensörü	1/4" Progressive Scan CMOS
Min. Aydınlatma	0.01Lux @(F1.2,AGC ON) ,0 Lux with IR 0.028Lux @(F2.0,AGC ON) ,0 Lux with IR
Shutter Hızı	1/3 s to 1/100,000 s
Lens	2.8mm@F2.0, Angle of view: 67.3° 4mm@F2.0, Angle of view: 53°
Lens Montajı	Pinhole

Day &Night	IR cut filter with auto switch
Wide Dynamic Range (WDR)	100 dB
Digital Noise Reduction (DNR)	3D DNR
<b>Sıkıştırma Standartı</b>	
Video Sıkıştırma	H.264 / MJPEG
H.264	Main Profile
Video Bit Oranı	32Kbps~8Mbps
<b>Görüntü</b>	
Maks. Çözünürlük	1280 × 720
Frame Oranı	50 Hz: 25 fps (1280 x 720), 25 fps (704 x 576), 25 fps (640 x 480)
Resim Ayarı	Saturation, Brightness, Contrast adjustable by client software or web browser
BLC	Yes, zone optional
ROI	Support
<b>Network</b>	
Network Depolama	NAS (Support NFS, SMB/CIFS)
Alarm Tetikleme	Intrusion detection, Line crossing detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Protokoller	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Genel	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standartlar	ONVIF, PSIA, CGI, ISAPI
<b>Arabirim</b>	
Bağlantı Arabirimi	1 RJ45 10M/100M Ethernet interface
<b>Genel</b>	
Çalışma Koşulları	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Güç Kaynağı	12VDC±10%
Güç Tüketimi	3W MAX
Boyutlar (mm)	37.3×41.4×24.3
Ağırlık	55g(0.12lbs)

## Boyutlar

