

DP-22CS54D7T-PH 1080p WDR Covert Camera



Key Features

- 2.0 megapixel progressive scan CMOS
- HD analog output, up to 1080p resolution
- OSD menu, DNR, AGC
- 120 dB true WDR
- Applicable for ATM machine

Specifications

Camera	
Image Sensor	2.0 megapixel progressive scan CMOS
Min. illumination	0.01 Lux@(F1.2, AGC ON)
Signal System	PAL/NTSC
Shutter Time	PAL: 1/25 s to 1/50, 000 s
	NTSC: 1/30 s to 1/50, 000 s
Effective Resolution	1920 (H) × 1080 (V)
Lens	3.7 mm @ F2.5 (2.8 mm Optional)
Field of View	69.5° (3.7 mm), 78.4° (2.8 mm)
Lens Mount	M12
Day & Night	Electronic
Frame Rate	1080p@25fps, 1080p@30 fps
Synchronization	Internal Synchronization
WDR	> 120 dB
Video Output	1 HD analog output
Menu	
AGC	High/Middle/Low/ Off
Day/Night Mode	AUTO/COLOR/WB (White and Black)
White Balance	ATW/MWB
Backlight Compensation	Support
WDR	Support
Function	Contrast, Sharpness, Color gain, Mirror, Digital noise reduction
General	
Operating Conditions	-40° C to 60° C (-40° F to 140° F) Humidity: 90% or less (no condensation)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1.5 W
Dimensions	32.4 mm × 32.4 mm × 22.0 mm (1.28" × 1.28" × 0.87")
Weight	Approx. 200 g (0.44 lb.)