

DP-22E16F7T-IT5 3MP WDR EXIR Bullet Camera



Key Features

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- True Day/Night
- OSD menu, DNR, Smart IR
- True WDR, up to 120dB
- EXIR technology, up to 80m IR distance
- IP66 weatherproof
- Up the Coax(HIKVISION-C)

Specifications

| Camera | |
|----------------------|---|
| Image Sensor | 3MP CMOS Image Sensor |
| Effective Pixels | 2052(H)*1536(V) |
| Min. illumination | 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR |
| Shutter Time | 1/25(1/30)s to 1/50,000s |
| Lens | 3.6mm, 6mm, 8mm, 12mm, 16mm optional |
| | Angle of View: 67.8°(3.6mm), 44.6°(6mm), 31.6°(8mm), 20.2°(12mm), 15.8°(16mm) |
| Lens Mount | M12 |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0° - 360°; Tilt:0° - 90°; Rotate: 0° - 360° |
| Synchronization | Internal Synchronization |
| WDR | 120dB |
| Video Frame Rate | 1920×1536@18fps |
| HD Video Output | 1 Analog HD output |
| S/N Ratio | >62dB |
| Menu | |
| AGC | Support |
| D/N Mode | Color/BW/SMART |
| White Balance | ATW/ MWB |
| BLC | Support |
| Functions | Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR |
| General | |
| Operating Conditions | -40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC± 15% |
| Power Consumption | Max. 5W |
| Protection Level | IP66 |
| IR Range | Up to 80m |
| Communication | Up the coax, Protocol: HIKVISION-C (TVI output) |
| Dimensions | 86.7mm×81.6mm×226mm (3.41 ×3.23 ×8.67) |
| Weight | Approx. 680g (1.5lb) |